

THE WATER-SOLUBLE, HUMAN SAFE, EARTH SAFE  
ENVIRONMENTALLY FRIENDLY  
DEGREASER/CLEANER.

NOTE:

This is not an acid/solvent product - DO NOT USE FULL STRENGTH - This is a water-activated product.

Suggested Mix Ratio - Unikleen to Water

Cold Solution Parts Tank -	1 to 4=32oz/Gal
Heated Parts Tank-	1 to 8=16oz/Gal
Heated/Spray Parts Tank-	1 to 32=4oz/Gal 1 to 64=2oz/Gal
Heated Power Sprayers-	1 to 32=4oz/Gal 1 to 64=2oz/Gal
Automatic Floor Scrubbers-	1 to 16=8oz/Gal 1 to 64=2oz/Gal
Mop & Bucket-	1 to 16=8oz/Gal 1 to 32=4oz/Gal
Cloth for Machine Wipe Down-	1 to 4=32oz/Gal 1 to 8=16oz/Gal 1 to 16=8oz/Gal

## Green Unikleen Dilution Ratios

Green Unikleen is a concentrated product. It must be diluted in water to activate the product. The following are recommended dilution ratios for a wide range of cleaning and degreasing tasks:

<b>TASK</b>	<b>SURFACES OR TYPE OF DIRT BEING CLEANED</b>	<b>DILUTION RATIO (Green Unikleen:Water)</b>
<b>Heavy Cleaning</b>	Auto Parts Cleaning	1:4 – 1:8
	Smoke	1:4 – 1:8
	Soot	1:4 – 1:8
	Heavy Grease	1:4 – 1:8
	Barbecue Grills	1:4 – 1:8
<b>General Cleaning</b>	Countertops (greasy)	1:16
	Painted Surfaces	1:16
	Floors	1:16
	Office Equipment	1:16
	Carpet Cleaning (by hand)	1:16
	Wood Paneling	1:16
	Upholstery	1:16
	Tile	1:16
<b>Cleaning with Equipment: Pressure washers, steam cleaners, carpet cleaners.</b>	Floor Scrubbing	1:64
	Concrete	1:64
	Car Wash	1:64
	Carpet Shampooing	1:64
	Pressure Washers (Vinyl and aluminum siding, etc.)	1:64
<b>Light Cleaning</b>	Windows	1:64-1:128
	Countertops (normal)	1:64-1:128
	Stainless Steel	1:64-1:128
	Chrome	1:64-1:128
	Plexiglass	1:64-1:128